RECONDITIONED

GRM-80STAMPING AND FORMING MACHINE





Technical Data:

- 1 Drive with frequency-controlled Simodrive motor NEW; max. 250 r.p.m.
- 1 Central gearwheel NEW
- 1 Material feed right-hand version with feed time reduction, cam-controlled; max. feed length 500 mm; max. strip width 80 mm
- 1 Central mandrel movement, positively cam-controlled; max. stroke 80 mm
- 1 Standard slide unit, right-hand; max. stroke 95 mm
- 3 Standard slide units, left-hand; max. stroke 95 mm
- 1 Narrow slide unit; max. stroke 70 mm
- 1 Two-point eccentric press unit; nominal force 300 kN; stroke 16 mm
- 1 Central lubrication unit
- 1 Pneumatic unit
- 1 Straightening unit BRA II/35
- 1 Process control VariControl Economy VC 1E NEW, consisting of:
- stand-alone control cabinet 700x700x1600 mm (WxDxH)
- electronic control and monitoring system
- operating unit with 15" TFT-Touch Display
- connection to machine via cable duct
- machine controller
- tool controller, 2 freely programmable modules with 8 channels, 1 valve module
- electronic hand-wheel
- intermediate wheels for linear manufacturing Pos. 9A and 15A

230.000,-Euro

